

CB-80

KEY FEATURES

Introducing our latest automated applicator technology: the CB-80, an intermittent motion applicator designed to efficiently apply the WaveGrip™ Cardboard Can Carrier at speeds of up to 80 cans per minute in 4, 6, and 8-pack formats. Its modular design minimizes the space requirement needed to operate, and the flexibility of the CB-80 ensures it scales as your business grows. The CB-80 can be adjusted to run multiple can heights of both 202/211 and 202/204 in sleek and standard cans. CB-80 applicators come with 12 month limited warranty.

DIMENSIONS

Weight	1700 Lbs approximate/770 kg
Frame size	66" L 35" W 84" H. +/- 3 1905mm(L) x 965.2mm(W) x 2006.6mm(H)
Conveyor Height	Models from 29" up to 50"

CONTROL SYSTEM

Operator Interface	Push Button
--------------------	-------------

IN-FEED OPTIONS

Left hand Single lane	1 can
Right hand Single lane	1 can
Inline Single lane	1 can

CARRIER OPTIONS

Standard 202/211 Can	4545 4pk / 3030 6pk / 2272 8pk
Sleek 202/ Can	5,262 4pk / 3508 6pk / 6,631 8pk
Can size	8oz, 12oz, 16oz, 19.2oz 200ml, 250ml, 310ml, 330ml, 355ml, 440ml, 473ml, 500ml, 568ml

MECHANICAL CONSTRUCTION

Electrical	110v single phase, 15A
Air	50l/min @ 5 bar 1.6 cfm, 80 psi
PLC	Allen Bradley
Interlocks	Allen Bradley 44N-Z2NRS1C
Standards	CE, CUL, ASME

MACHINE LAYOUT

Output Format	4, 6, 8 (short side leading)
Fault Identification	Light on Operator Station
In-feed options	Left hand Single lane / 1 can Right hand Single lane / 1 can Inline Single lane / 1 can
Machine Access Panels	4 Swinging Doors

OPTIONAL ADD-ONS

Leg extensions

*The information in this spec sheet is provided for general informational purposes only. We make no warranties, express or implied, regarding accuracy, reliability, or suitability. Errors may exist, and information is subject to change without notice. We do not guarantee error-free content or continuous availability.



1-888-208-4626
sales@vincoautomation.com
www.vincoautomation.com